

Exhaust Hose NFC-4.2

High temperature Vehicle Exhaust Extraction Hose





NFC-4.2 Hose

NFC 4.2 Exhaust Hose for Vehicle Exhaust Extraction. Suitable for temperatures up to 420 C / 800 F.

- \bullet Suitable for Temperatures up to 420 C / 800 F
- Durable polyurethane coated E-Glass construction
- Durable Steel Helix

Product name	Exhaust Hose NFC-4.2		
Installation	[Indoor]		
Material	Polyurethane coated e-glass		
Suitable for combustible dust	False		
Operating Temperature	420 C/ 800 F		
Colour	Gray		



Exhaust Hose NFC-4.2

Description	Diameter, hose (in)	Hose length (ft)	[model]
NFC-4.2 Hose Ex 125mm (5 in) / 7.5 m (24 ft)	125mm / 5 in.	7.5m / 24 ft	86900688*
NFC-4.2 Hose Ex 100mm (4 in) / 10 m (33 ft)	100mm / 4 in	10m/33ft	86900685**
NFC-4.2 Hose Ex 100mm (4 in) / 7,5 m (24 ft)	100mm / 4 in.	7.5 m / 24 ft	86900684***
NFC-4.2 Hose Ex 125mm (5 in)/5m (16 ft)	125mm / 5 in	5m / 16 ft	86900687**
High temperature hose for vehicle exhaust extraction	125mm / 5 in.	10m/33ft	86900689*
NFC-4.2 Hose Ex 152mm (6 in)/ 5m (16 ft)	152mm / 6 in	5m / 16 ft	86900691****
NFC-4.2 Hose Ex 150mm (6 in) / 7.5m (24 ft)	150mm / 6 in	7.5m / 24 ft	86900692****
Hose Ex NFC-4.2 HT800 QS 150mm/10m			86900693
NFC-4.2 Hose Ex 200mm (8 in) / 5m (16 ft)	200mm/8in	5m / 16 ft	86900694****
NFC-4.2 Hose Ex 200mm (8 in) / 7.5m (24 ft)	200mm / 8 in	7.5m / 24 ft	86900695****
NFC-4.2 Hose Ex 200mm (8 in) / 10m (33 ft)	200mm / 8 in	10m/33 ft	86900696****
NFC-4.2 Hose Ex 100mm/5 m			86900683

^{*}not suitable for dyno testing or DPF regeneration processes
**Not suitable for dyno testing or DPF regeneration processes.
***Not suitable for dyno testing or DPF regeneration processes
****Not suitable for dyno testin or DPF regen processes
****not suitable for dyno testing or DPF regen processes